

Appln No. 09/747,677

Amdt date April 23, 2004

Reply to Office action of December 23, 2003

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1-51. Cancelled

52. (Currently Amended) A hyperlinked video broadcast system including a plurality of multiplexed video streams each having a plurality of video frames, said system comprising:

a mask generator generating a plurality of mask overlays corresponding to a plurality of regions in said plurality of video frames; and

B' a receiver ~~capable of~~ receiving viewer actuation of stream selection input identifying one of said plurality of mask overlays selected by a viewer and switching from presenting to said viewer a first one of said plurality of multiplexed video streams to presenting to said viewer a second one of said plurality of multiplexed video streams in response to said viewer actuation stream selection input.

53. (Currently Amended) The system of claim 52 wherein information associated with said viewer actuation stream selection input is reported to a remote location via a backchannel communications connection.

Appln No. 09/747,677

Amdt date April 23, 2004

Reply to Office action of December 23, 2003

54. (Previously Presented) The system of claim 52 wherein said plurality of mask overlays comprise location and shape information of said plurality of regions in said plurality of video frames.

55. (Currently Amended) A hyperlinked video and audio broadcast system including a plurality of multiplexed video streams each having a plurality of video frames and including a plurality of multiplexed audio streams, said system comprising:

a mask generator generating a plurality of mask overlays corresponding to a plurality of regions in said plurality of video frames; and

B1
Cont.
a receiver ~~capable of~~ receiving viewer actuation of stream selection input identifying one of said plurality of mask overlays ~~selected by a viewer~~ and switching from presenting to said viewer a first one of said plurality of multiplexed audio streams to presenting to said viewer a second one of said plurality of multiplexed audio streams in response to said viewer actuation stream selection input.

56. (Currently Amended) The system of claim 55 wherein information associated with said viewer actuation stream selection input is reported to a remote location via a backchannel communications connections.

57. (Previously Presented) The system of claim 55 wherein said mask overlays comprise location and shape information of said plurality of regions in said plurality of video frames.

Appln No. 09/747,677

Amdt date April 23, 2004

Reply to Office action of December 23, 2003

58. (Currently Amended) A hyperlinked video reception system including a plurality of input multiplexed video streams each having a plurality of video frames, said system comprising:

a mask presenter rendering a plurality of mask overlays corresponding to a plurality of regions in said plurality of video frames;

a receiver receiving ~~stream selection input from a viewer~~ actuation of specifying a first one of said plurality of input multiplexed video streams by identifying one of said plurality of mask overlays,

wherein said receiver switches from presenting to said viewer a second one of said plurality of multiplexed video streams to presenting to said viewer a said first one of said plurality of multiplexed video streams in response to said viewer actuation ~~stream selection input~~.

59. (Currently Amended) The system of claim 58 wherein information associated with said viewer actuation ~~stream selection input~~ is reported to a remote location via a backchannel communications connections.

60. (Previously Presented) The system of claim 58 wherein said mask overlays comprise location and shape information of said plurality of regions in said plurality of video frames.

61. (Currently Amended) A hyperlinked video stream switching data structure system having a plurality of video

Appln No. 09/747,677

Amdt date April 23, 2004

Reply to Office action of December 23, 2003

streams each including a plurality of video frames said system comprising:

a plurality of video stream identifiers each associated with one of said plurality of video streams;

a plurality of mask overlays corresponding to a plurality of regions in said plurality of video frames;

a first data structure element referenced by a set of said plurality of mask overlays;

a second data structure element referenced by said first data structure element, said second data structure element containing a reference to a first one of said plurality of video streams; and

a current video stream identifier corresponding to a second one of said plurality of video streams;

wherein actuation ~~selection~~ of said one of said plurality of mask overlays by a viewer causes said system to make said current video stream identifier correspond to said first one of said plurality of video streams.

62. (Previously Presented) The system of claim 61 wherein said mask overlays comprise location and shape information of said plurality of regions in said plurality of video frames.

63. (Previously Presented) The system of claim 61 wherein said reference to a first one of said plurality of video streams references a third data structure element including references to an audio stream and a private data stream associated with said first one of said plurality of video streams.

Appln No. 09/747,677

Amdt date April 23, 2004

Reply to Office action of December 23, 2003

64. (Currently Amended) A method for switching between multiplexed video streams in a hyperlinked video broadcast system including a plurality video streams each having a plurality of video frames, said method comprising:

generating a plurality of mask overlays corresponding to a plurality of regions in said plurality of video frames;

receiving viewer actuation of ~~stream selection input~~ identifying one of said plurality of mask overlays by a viewer; and

switching from presenting to said viewer a first one of said plurality of multiplexed video streams to presenting to said viewer a second one of said plurality of multiplexed video streams in response to said viewer actuation ~~stream selection~~ input.

65. (Currently Amended) The method of claim 64 further comprising reporting information associated with said viewer actuation ~~stream selection input~~ to a remote location via a backchannel communications connection.

66. (Previously Presented) The method of claim 64 wherein said plurality of mask overlays comprise location and shape information of said plurality of regions in said plurality of video frames.

67. (Currently Amended) A method for switching between multiplexed audio streams in hyperlinked video broadcast system

Appln No. 09/747,677

Amdt date April 23, 2004

Reply to Office action of December 23, 2003

including a plurality video streams each having a plurality of video frames and including a plurality of audio streams, said method comprising:

generating a plurality of mask overlays corresponding to a plurality of regions in said plurality of video frames;

receiving ~~stream selection input from a viewer~~ actuation of specifying a first one of said plurality of input multiplexed audio streams by identifying one of said plurality of mask overlays; and

switching from presenting to said viewer a second one of said plurality of multiplexed audio streams to presenting to said viewer a ~~said~~ first one of said plurality of multiplexed audio streams in response to said viewer actuation ~~stream selection input~~.

68. (Currently Amended) The method of claim 67 further comprising reporting information associated with said viewer actuation ~~stream selection input~~ to a remote location input via a backchannel communications connections.

69. (Previously Presented) The method of claim 67 wherein said mask overlays comprises location and shape information of said plurality of regions in said plurality of video frames.

70. (Currently Amended) A method for switching between video streams in a hyperlinked video reception system including a plurality of input multiplexed video streams each having a plurality of video frames, said method comprising:

Appln No. 09/747,677

Amdt date April 23, 2004

Reply to Office action of December 23, 2003

rendering a plurality of mask overlays corresponding to a plurality of regions in said plurality of video frames;

receiving ~~stream selection input from a viewer~~ actuation of specifying a first one of said plurality of input multiplexed video streams by identifying one of said plurality of mask overlays; and

switching from presenting to said viewer a second one of said plurality of multiplexed video streams to presenting to said viewer a ~~said~~ first one of said plurality of multiplexed video streams in response to said viewer actuation ~~stream selection input~~.

B!
cont.
71. (Currently Amended) The method of claim 70 further comprising reporting information associated with said viewer actuation ~~stream selection input~~ to a remote location via a backchannel communications connection[s].

72. (Previously Presented) The method of claim 70 wherein said mask overlays comprises location and shape information of said plurality of regions in said plurality of video frames.

73. (Currently Amended) A method for switching between hyperlinked video streams in a hyperlinked video stream system having a plurality of video streams each including a plurality of video frames said method comprising:

generating a plurality of video stream identifiers each associated with one of said plurality of video streams;

Appln No. 09/747,677

Amdt date April 23, 2004

Reply to Office action of December 23, 2003

generating a plurality of mask overlays corresponding to a plurality of regions in said plurality of video frames;

generating a first data structure element referenced by a set of said plurality of mask overlays;

generating a second data structure element referenced by said first data structure element, said second data structure element containing a reference to a first one of said plurality of video streams;

generating a current video stream identifier corresponding to a second one of said plurality of video streams;

receiving viewer actuation of ~~stream selection input~~ ~~identifying~~ said one of said plurality mask overlays; and

making said current video stream identifier correspond to said second one of said plurality of video streams in response to said viewer actuation ~~stream selection input~~.

74. (Previously Presented) The method of claim 73 wherein said mask overlays comprise location and shape information of said plurality of regions in said plurality of video frames.

75. (Previously Presented) The method of claim 73 wherein said reference to a first one of said plurality of video streams references a third data structure element including references to an audio stream and a private data stream associated with said first one of said plurality of video streams.

Appln No. 09/747,677

Amdt date April 23, 2004

Reply to Office action of December 23, 2003

76. (New) A hyperlinked video broadcast system including a plurality of multiplexed video streams each having a plurality of video frames, the system comprising:

means for generating, in response to a user command, an image overlay visually identifying an object in a video frame;

means for receiving viewer actuation of the image overlay;
and

means for switching from presenting to a viewer a first one of the plurality of multiplexed video streams to presenting to the viewer a second one of the plurality of multiplexed video streams in response to the viewer actuation.

B1
cont
77. (New) The system of claim 76, wherein the image overlay is associated with first timing data, presentation of the image overlay being synchronized with the video frame based on the first timing data.

78. (New) The system of claim 77 further comprising a computer-readable medium storing computer program code that compares the first timing data with second timing data associated with a current video frame and sleeps for a period of time equivalent to a difference in times indicated by the first and second timing data, the computer program code being awakened for visually identifying the object based on the image overlay in response to an expiration of the time period.

79. (New) The system of claim 76 further comprising:

Appln No. 09/747,677

Amdt date April 23, 2004

Reply to Office action of December 23, 2003

a data store storing a data structure including annotation data associated with the object, the data structure being associated with second timing data indicative of a last instance the data structure is used in a video program associated with the video frame; and

means for removing the data structure from the data store in response to a determination based on the second timing data that the data structure is no longer used in the video program.

80. (New) The system of claim 79 further comprising:

means for encoding the data structure and image overlay data into a packet stream received by a receiver in the hyperlinked video broadcast system.

81. (New) The system of claim 80 further comprising:

means for encoding the image overlay data and the data structure into a portion of the packet stream that is received prior to receipt of a portion of a video signal including the video frame.

82. (New) The system of claim 81, wherein a fixed number of packets is allocated to each of a plurality of image overlay data sets to be encoded into the packet stream, the fixed number of packets corresponding to a number of packets filled by a largest image data set to be encoded.

Appln No. 09/747,677

Amdt date April 23, 2004

Reply to Office action of December 23, 2003

83. (New) The system of claim 82, wherein a particular image overlay data set fills a particular number of packets that is less than the fixed number of packets.

84. (New) The system of claim 83, wherein the data structure is encoded into the packet stream by identifying a first occurrence of the object associated with the data structure, and moving backwards in time from the first identified occurrence and filling one or more unused packets allocated to the particular image overlay data set with at least a portion of the data structure.

B¹
out.
85. (New) The system of claim 84, wherein the packet stream is received with a video stream over a broadcast signal.

86. (New) The system of claim 84, wherein the packet stream is received out-of-band separately from a video stream including the video frame.

87. (New) The system of claim 84, wherein the means for generating an image overlay further comprises:

means for identifying on a first two-dimensional section containing a three-dimensional volume, a first region associated with the object, the first region including one or more first pixels;

means for filling the first region including the one or more first pixels with a predetermined value;

Appln No. 09/747,677

Amdt date April 23, 2004

Reply to Office action of December 23, 2003

means for moving in a first direction along a third dimension to a second two-dimensional section containing the three-dimensional volume;

means for determining whether a second pixel in the second two-dimensional section that corresponds to a filled pixel in the first two-dimensional section belongs to the three-dimensional volume;

BI
cancel.
means for filling a second region including the second pixel in the second two-dimensional section with the predetermined value;

means for returning to the first two-dimensional section;
and

means for moving in a second direction along the third dimension to a third two-dimensional section containing the three-dimensional volume for filling a third region.

88. (New) The system of claim 87, wherein each two-dimensional section is a video frame.

89. (New) The system of claim 87, wherein the third dimension is time.
